Interface:

Humidity:

dimension (mm)

weight

Working Temperature:

Weight:

Size:

Mini Thermal Printer BABY220	
Model: BABY220	Features
	It applies mobile printing to support the application, and suitable to outdoor work environments.
	It has small size light weight reliable performance simple to connect easy to operate. Support windows/andorid via bluetooth/USB/Serial interfaces.
-=00	Low operating costs (no ribbons, ink cartridges)
	easily set in various equipment, such as The mobile police system, The tobacco distribution system, The utility meter reading system, The mobile office / mobile logistics systems The portable instrumentation, The testing equipment, ncillary equipment.
Specifications	
Printing Method:	Direct Thermal
Speed:	50-80mm/sec
Reliability TPH Life:	100km
Resolution:	203DPI (8dot/mm)
Printing Width:	48mm (384dot)
Paper Width:	58±01mm
Roll Diameter:	φ≤40mm
Paper Type:	Thermal Paper
Power:	rechargeable lithium battery/NI-MH battery
Battery:	Lithium: 7.4VDC/1500mAH
Charging mode:	DC 9V/1.5A
Print parameters:	support to download the Logo trademark
Printing Chinese character:	Chinese: simplified Chinese 24x24 point.
	ANK: ASC11 12 ×24
Extended character table:	OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/
	West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/
	OEM852/OEM858/Iran II/Latvian/Arabic/PT1511251/
	OEM747/WPC1257/Vietnam/OEM864/
	Hebrew/WPC1255/Thai
Emulation:	ESC/POS command
	standard DC222/IJCB Blustooth 2 0/CDB agreement or

standard RS232/USB, Bluetooth 2.0/SPP agreement or

infrared/IRCOMM agreement (optional).

134g

10~90%

105*75*45mm -10~50℃

200g (including battery)

110X85x45 (LxWxH)