

HS-2410A Spec Sheet



System Configuration	
Processor	Intel Bay Trail Dual Core Celeron up to 2.16GHz, 1M Cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	SSD or eMMC module
Power Supply	12V / 60W
OS support	Android 4.x
Display & Touch	
LCD	9.7" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with 10 pts multi-touch support
I/O & Expansion	
Serial Port	3, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port	1
Standard USB Port	4, 1 x USB 3.0/2.0 + 3 x USB 2.0
LAN Port	10 / 100 / 1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	N/A
UPS Port	N/A
Audio	Line-out x 1

Internal Expansion Slot	mini-PCIe slot x 1
Environmental	
Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

- Please note that this specification is pre-production spec, and is subjected to change without notice