

Customer Line Display



PD-300 Series

- LCD Customer Line Display
- Blue character and yellow background
- Two-line display with 20 characters per line
- Large character size for easy viewing : 6.0 mm x 9.6 mm
- 15°, 30° and 45° tilt angle adjustment
- Command emulations support : PST (POSIFLEX proprietary command) & ESC/POS
- Dimension : 220 mm (W) x 110 mm (D) x 410 mm (H);
Weight : 0.84 kg for standalone PD-300R

PD-300R : Standalone (300 mm pole), 270° horizontal swivel, Serial interface

PD-302 : Rear-mount for POSIFLEX TP series terminal, Serial interface

PD-305 : Base-mount for POSIFLEX terminal with 5th generation base, Serial interface

PD-308R : Rear-mount with pole (200 mm) for POSIFLEX FT series terminal, Serial interface

PD-308UE : Rear-mount with pole (200 mm) for POSIFLEX FT series terminal, USB HID & USB Virtual COM selectable

PD-309UE : Base-mount with pole (200 mm) for POSIFLEX terminal with 6th / 7th / 8th generation base / 10" & 12" KS terminal / XP series and DT series, USB HID & USB Virtual COM selectable

PD-310UE : Rear-mount for POSIFLEX 10"/12"/15"/17" KS series terminal, USB HID & USB Virtual COM selectable

PD-330UE : Rear-mount for POSIFLEX XP series terminal, USB HID & USB Virtual COM selectable

PD-340UE : Rear-mount for POSIFLEX HS series terminal, USB HID & USB Virtual COM selectable

PD-350UE : Rear-mount for POSIFLEX XT series terminal, USB HID & USB Virtual COM selectable

PD-340R : Rear-mount for POSIFLEX XT series terminal, Serial interface

PD-350R : Rear-mount for POSIFLEX XT series terminal, Serial interface



PD-2300 / PD-2300U

- VFD Customer Line Display
- Green or Blue screen filter
- Adjustable pole height
- Two-line display with 20 characters per line
- Large character size for easy viewing : 9.03 mm x 5.25 mm
- 14.5° and 30° tilt angle adjustment
- Near 360° horizontal swivel adjustment
- Various command emulations selectable by DIP switch : ADM, Aedex, ESC/POS, Futaba, Noritake, UTC
- 12 international character sets support
- Interface : Serial (PD-2300) or USB (PD-2300U)
- Dimension : 260 mm (W) x 110 mm (D) x 291 mm ~ 426 mm (H);
Weight : 0.93 kg



PD-6x07U Series

- 7" Graphical Customer Line Display
- TFT LCD panel with resolution up to 800 x 480
- 20 x 2, 20 x 4, 30 x 4 characters support
- Adjustable font and background color
- JPEG graphics display support
- Command emulations support : ADM, Aedex, ESC/POS, Futaba, Noritake, UTC
- Dimension : 471 mm (H) x 221.5 mm (W) x 188 mm (D);
Weight : 0.86 kg for standalone PD-6207U

PD-6207U : Standalone (300 mm pole)

PD-6307U : Terminal rear-mount for POSIFLEX 15"/17" KS series terminal

PD-6507U : Terminal rear-mount for POSIFLEX HS series terminal

PD-6607U : Terminal rear-mount for POSIFLEX XT series terminal