

• Equipped with Intel advanced CPUs

• green design with low power consumption

• IP54 dust & water proof

• Tool-free installation for stand



POS-385H

15" POS Terminal

Features



Easy service & maintenance of HDD & components





Second Display 8.4" Touch



Covered side for optional I/O

POS-385H





Specification

Processor	Pentium DUAL CORE G850 2.9G, L2 3M, 65W	Sandy bridge Core i3 2120-3.30Ghz CPU
Chipset	Intel [°] H61	
System Memory	1 X DDR 3, 2 GB	
Graphic Memory	Intel HD Graphics 3000/2000, integrated in CPU,	
·	frequency 850MHz (dynamic up to 1.1GHz)	
LCD Panel		
LCD Size	15" TFT LCD	
Brightness	250 cd/m ²	
Resolution	1024x768	
Touch Screen	Resistive	
Tilt Adjustment	0° ~ 65°	
Storage Device		
Hard Drive	160 GB or higher	
Expansion		
miniPCI-E Socket	1	
External I/O		
USB 2.0	4 v. P. 145 COM parts (COM) standard PC222 COM DC2221/02/495 COM2/4	
Serial Port	4 x RJ45 COM ports (COM1 standard RS232; COM2 RS232/422/485; COM3/4	
Parallel Port	powered RS232; COM3 default 5V / COM4 default 12V by BIOS setting) 1 (DB25 female)	
GigaLAN (10/100/1000)	1 (RJ45) (H61)	
DC Jack	1	
VGA	1 (DB15 female)	
Cash Drawer	1 (RJ11)	
Audio Jack	1 x Line-out	
Power Adapter	420\\\/	19V (6.3A)
Control / Indicator	12000/	13V (U.SM)
Power Button	1	
Indicator LED	1	
Peripheral (option)		
MSR	3 Tracks MSR	
Second Display	8.4" Touch	
Customer Display	Flush mount VFD display 2 x 20 characters (COM)	
Certificate		
EMC & Safety	FCC Class A / CE Mark / LVD	
OS Supported		
	Windows XP, POS Ready 2009, XP Embedded, XP professional for Embedded, Linux,	
	Windows'7, P	

Essae-Teraoka Pvt. Ltd.



410, 100ft Road, 4th Block, Koramangala, Bengaluru-560 034



info@essae.com



http://www.essae.com



+91 80 3021 3021



+91 80 3021 3001



1-800-425-3111 0-78488 12346



Your Essae representative



▲ Factories in Bengaluru and Goa ▲ 47 Branch Offices ▲ 250+ Service engineers ▲ 350+ Resellers/Partners