

BP-3 Thermal Portable Printer



Compatible With
Posiflex **MT- 4008** &
with all mobile computing
devices.



- 3' Inch Portable Thermal Printer.
- Mini size, double injection molding for the rugged usage.
- Non-slip design (salient points on the rubber of the two sides).
- Support USB, power adapter or mobile power charging.
- Has standby mode to save power with Exclusive power indication light
- Provide SDK for IOS, Android & Windows

Thermal Portable Printer BP-3- Specifications

Color	Orange / Gray
Printing way:	Thermal Line printing
Paper width:	80mm
Printing width:	72 mm
Resolution:	203dpi(8 dot/mm)
Printing speed:	75 mm/s (max)
Dot /line:	576 dots/line
Print Font	ASCII Font A: 12×24/ASCII Font B: 9×17/Chinese: 24×24
Characters per Line	Font A: 48/Font B: 64/Chinese: 24
Rolling paper Diameter:	ϕ 40(max)X80mm
Paper feeding method:	Easy paper loading
Barcode type:	CODE39/EAN-13/EAN-8/CODABAR/CODE93/ITF /QR/PDF417
MCBF:	5 Million Lines
Print head lifespan:	50 km
Interface:	Bluetooth(BT4.0&BLE)/WiFi/USB/RS232
Paper out alarm:	Support
Printing Command:	ESC/POS
Battery:	2000 mAh rechargeable li-ion battery
	Lifespan is more than 500 times
	Continuously working for 3 hours or 100m
Power Supply:	4-6 hours charging time
Power alarm:	USB/Power adapter/mobile power charging
Dimension(LxWxH) :	Battery need to be charged or changed when battery light turns off and red light turns on
Weight:	113×103×45(mm)
Environment parameters:	335g (including the paper roll and battery)
	Working temperature: -10°C ~ 50°C
	Working humidity: 20% ~ 85%
	Storing temperature : -20°C ~ 70°C
Environment parameters:	Storing humidity: 5% ~ 95%