

Key Features

- ▶3" high-speed thermal printer with auto and additional manual cutters
- ▶Detailed curvy surface in a stylish design
- ▶External cover for spill-resistant design (Optional)
- ▶Printing speed up to 220 mm per second in low-noise printing
- ▶High-resolution print up to 8 dots / mm and 576 dots / line
- ▶80 or 58 mm paper width support
- ▶QR code printing support
- ▶User-friendly WiFi support without cable for easy setup
- ▶Compact size and light weight for easy placement
- ▶Desktop or wall-mount solution for flexible deployment
- ▶Drop-and-load structure for easy paper loading
- ▶Control over 2 cash drawers through 1 port
- ▶Enhanced capability in kitchen bell for reminder function



Spill-resistant cover

AURA-8800

3” High Performance WiFi Thermal Printer



The AURA-8800 is a high performance model with printing speed up to 220 mm per second. As a receipt and information printer, its speedy printing satisfies crowded check-out line and promotional activities in the peak hours. Optional spill-resistant top cover displays thoughtful design for retailers to run their business smoothly even in the harsh environments like pub, bar, etc. Additionally, the AURA-8800 features easy paper replacement and flexible deployment in the wall-mount design.

The AURA-8800 showcases high reliability for harsh and busy applications.

Specification	AURA-8800
Print Speed	220 mm / sec (Max.)
Print Resolution	8 dots / mm, default 512, 576 (Max.) dots / line
Paper Width	80 (Or 58) + 0 / -1 mm
Printing Width	64 mm (For 512 dots / line) / 72 mm (For 576 dots / line)
Input Buffer	6 KB
LED indicator	Power : Green, Error : Red, Paper Out : Red
Cutter	Auto cutter & Manual cutter
Power Supply	24V DC power adaptor, 60W
Paper Spacing Plate	For 80 or 58 mm paper width
Interface	USB (Optional Serial, Parallel, LAN port or Wireless)
Dimension (W x D x H in mm)	148 x 205 x 143
Weight (N. w. in kg)	1.2
Color	Ivory, White or Black
Language Support	
International Character Set	15 international character sets supported (Denmark I, Denmark II, Ex-Yugoslavia, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain, Spain II, Sweden, UK, USA)
Character Code Page	23 code pages supported (Power on default code page can be set infactory by software program)
Bar Code Printing	UPC-A/E, EAN13/8, ITF, CODE39/93/128, CODABAR, QR Code, PDF417
Options	
Kitchen Bell	Alarm type KL-100 or buzzer type KZ-200
Wall Mount Kit	Yes
Spill-Resistant Cover	Yes
Certifications	
FC CE SGS TÜV SÜD RoHS REACH Windows Embedded Partner SAP ORACLE	

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2013 AURA88Q2C1

** The product information and specifications are subject to change without prior notice.