Sweets Mart and Namkeen Shop - POS

www.easovation.com 09624045500



www.easovation.com www.easo.co.in easovation@gmail.com +919624045500







- Android All in One POS
- 15" LCD Display Aluminum Housing
- All in One Design
- Android Solution















Mobile Printer BABY 380

Main Features





- 1. It has small size, light weight, reliable performance, simple to connect.easy to operate. Support windows/ android via bluetooth/USB/Serial interface.
- 2. Easily set in various equipment, such as The mobile police system, The tobacco distribution systems, The utility meter reading system, The monile office/mobile logistics systems. The portable instrumentation. The testing equipment, ncillary equipment.
- 3. It applies mobile printing to support the application, and suitable to outdoor work environments.
- 4. Low operating costs into ribbons, ink cartridges







■ Technical Specifications

Model Number	BABY 380	
Printing method	Direct thermal	
Speed	80mm/s(average)	
Reliability TPH life	100km	
Resolution	203DPI(8 dots/mm,576 dots/line)	
Printing width	72mm	
Paper width	80±01mm	
Roll diameter	Ø≤60mm	
Paper type	Thermal paper	
Power	DC7.4V,2A rechargeable Li-ion battery	
Battery	Lithium:7.4VDC/2000mAH	
Charging mode	DC 9V/1.5A	
Print parameters	Suport to download the logo trademark	
Printing chinese character	Chinese simplified Chinese 24x24 point ANK:ASCII 12x24	
	OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/Greek/Hebrew/East	
Extended character table	Europe/Iran/WPCI252/OEM866/OEM852/OEM858/Iran II/Latvian/Arabic/PT1511251/	
	OEM747/WPCI257/Vietnam/OEM864/Hebrew/WPC1255/Thai	
Emulation	ESC/POS command	
Interface	Standard RS232, USB,Bluetooth	
Weight	134g	
Size	105 x75 x45 mm	
Working temperature	−10~50°C	
Humidity	10~90%	
Weight	620g(Including accessories)	
Dimension(mm)	103x99x46(LxWxH)mm	



MTP-25 & MTP-85

Bluetooth Printer

SPECIFICATIONS OF WePMTP-25&MTP-85



Features of MTP-25

- · Drop in paper loading, easy operation
- · Support to print receipt during charging the battery
- Bluetooth : BT3.0 and BLE4.0
- . Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- Print Method : Direct thermal line
 Dot Density : 384 dots/line
 Print Speed : 60mm/s (Max)
- . Interface : USB+Bluetooth (Standard) +Android
- Paper Width: 58mm • Paper Diameter: 50mm
- Print Commands : Compatible with ESC/POS
- Barcode Type: UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- . Buffer: Input buffer 4K bytes NV Flash 60K bytes
- Dimension: 148.5(L) X 86(W) X 58.5(H)mm
- Weight (including battery): 288g
- Power Adaptor: Input AC100-220V; Output DC9V/1A
- Battery: 1800mAh, 7.4V rechargeable Li-ion Battery
- Charging Time: 2.5~3.5 hours
- Work Environment : Temperature: $0 \sim 45^{\circ}\text{C}$; Humidity: $10 \sim 80\%$
- Storage Environment : Temperature: 10 ~ 60°C; Humidity: 10 ~ 90%
- Thermal Mechanism: 50KM

Features of MTP-85

- . Drop in paper loading, easy operation.
- · Support to print receipt during charging the battery.
- . Bluetooth: BT3.0 and BLE4.0
- · Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- Print Method : Direct thermal line
 Dot Density : 576 dots/line
 Print Speed : 60mm/s (Max)
- Interface : USB+Bluetooth (Standard) +Android
- Paper Width: 80mmPaper Diameter: 50mm
- Print Commands : Compatible with ESC/POS
- Barcode Type: UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- . Buffer: Input buffer 4K bytes NV Flash 60K bytes
- Dimension: 131(L) X 107(W) X 58(H)mm
- Weight (including battery): 350g
- Power Adaptor : Input AC100-220V; Output DC9V/1A
- Battery: 2200mAh, 7.4V rechargeable Li-ion Battery
- Charging Time: 3.0~5.0 hours
- Work Environment : Temperature: 0~45°C; Humidity: 10~90%
- Storage Environment : Temperature: 10 ~ 50°C; Humidity: 10 ~ 90%
- Thermal Mechanism : 50KM



- Small & comfortable to carry
 - Easy paper loading & User friendly with classic three-button
- USB + Bluetooth interface (standard)
 + Android
- LED indication facility available during abnormal condition of printer

Fruits & Vegetables - POS Billing Software

www.easovation.com 09624045500



www.easovation.com 09624045500





Credit & Debit Card Swipe Machine



Ethernet Thermal Printer: GP-U80300I







Specification

Print Method:	Direct thermal printing
Emulation:	ESC/POS & Line/T command sets compatible
Paper width:	80mm
Print width:	72mm
Dot density:	203dpi
Paper roll:	80mm width, 83mm diameter max.
Print speed:	300mm/sec max.
Paper thickness:	0.06~0.08mm
Interface:	Serial + USB + Ethernet, or Parallel + USB
Data buffer:	128K bytes
Barcode type:	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODEBAR /CODE93/CODE128/QR Code
Power supply:	DC24V/2.5A
Cash drawer:	DC24V/1A
Print head life:	150KM
Auto cutter life:	1.5 million cuts
Operating system:	Windows, OPOS, Linux
Net Weight:	1.25kg
Dimension:	175×140×137mm







Credit & Debit card swipe Machine

+91 9624045500 www.easo.co.in

easovation@gmail.com www.easovation.com

Fast Food Restaurant POS

www.easovation.com 09624045500



Fast Food Restaurant POS

www.easovation.com 09624045500







Ipos Bluetooth Thermal Printer



Technical specifications:

Paper Working	Loading way	easy
	Cutting way	Divulsion (dentiform)
Printer Performance	Print method	direct thermal print and auto paper feed
	Printing density	384 dots/line
	Filliding density	8 dots/mm
	Printing width	48 mm
	Max printer speed	85 mm/s(max.)
	Dot distance	0.125 mm
	Word size(WxH mm)	0.75×1
Drawing/Bar code	ASCII Character(WxH dots)	16 lattice:8×16; 24 lattice:12×24
Drawing/Bar code	ASCII Size(WxH mm)	16 lattice:1×2; 24 lattice:1.5×3
	Drawing/bar code	suitable
Testing Method	Lacking paper testing	photo electricity sensor
	Printer interface	TTL,RS232,bluetooth
Control System	Buffer	32k
	Command system	ESC printer command/WH printing command
Power	Working voltage	DC3.5V9V (from7.2-7.5V,with highest speed and excellent effect
	Current	2.5A-3A
Printer Mechanism	Printing head lifespan	60km
	Paper item	thermal paper
D	Paper width	58mm
Paper	Paper thickness	65±5um
	Diameter of paper roll	40mm
Environment	Operating temperature/humidity	0~50°C/10%~80% RH
	Storage temperature /humidity	-20~60℃, 10%~90% RH
Physics Specification	Dimension (WxHxD mm)	76.8mm*77.4mm*43.5mm
Warranty		1 year











K-CASH ECH410

Cash Drawer

Cash drawers are one of the core components to every Point of Sale System including: fast food, hospitality, fine dining, gasoline service stations, mass merchandising, convenience stores, lottery terminals, and general retail applications.

Main Features:

- · Rugged structure with reinforced heavy steel
- Adjustable bill \ coin compartment
- . Durability for 4 million operation
- · Wobble-free Drawer moment
- · Three -positions lock for maximum cash security
- · Anti-scratch surface
- · Screwless design metal casing
- · Ready for OLE POS (OPOS) OCXdriver

Color Avaible:



Technical Specifications

Model Number	K-CASH ECH410	
Dimensions (inch)	16.1"W x 16.3"D x 3.9"H (inch, without Feet)	
Dimensions (mm)	410 W x 415 D x 100 H (mm, without Feet)	
Drawer	Metal cash drawer with heavy-duty ball bearing roller	
Casing	Steel construction	
Front Panel	Steel construction with painted front or stainless steel front (option)	
	Usually the price is for the painted front. If a stainless steel front, the price should be 3.5USD plused.	
Bill Tray	Metal bill clips	
	Adjustable dividers for up to 5 compartments (with 5 metal clips)	
Coin Tray	Removable tray from the money case	
	Solo-row tray adjustable dividers for 5 compartments	
	Double-row tray with adjustable dividers for 8 up comartments	
Media slot	Front access slot for check, credit card receipt or any paper	
Lockable Lid	Lockable Lid for the cash receiver to change tray (option)	
Lock	3-position Key Lock	
Micro Switch / Sensor	Open by driver signal to the solenoid (option)	
I/O Interface	12V, 24V for RJ11 / RJ12 Receipt Printer Interface	
	9-Pin RS-232 Interface (option)	
	USB Interface (option)	
Durability	1,000, 000 operations	
Colour	Ivory , Black or Customization	
Packaging	465 W x 460 D x 150 H (mm)	
	18.3"W x 18.1"D x 5.9"H (inch)	
Net Weight	7.15 kgs	
Gross Weight	8.15 kgs	











K-SCAN LG100

Handheld Laser Barcode Scanner

The latest technology of hand-held barcode scanners provide intuitive scanning of the barcodes found in real-world environments. Our scanners ensures only the highest quality marks enter the supply chain, we have a variety of hand-held scanning solutions to meet business needs.

Main Features:

- · Stationary device
- RS232, PS/2, USB
- 120 scans/sec
- · Product compliance: RoHS, FCC, CE, IEC801-2

Color Avaible:

Technical Specifications

Scan Performance	
Scan mode	Automatic handheld
Alarm mode	LED light alarm, buzzer alarm
Read rate	120 scans/sec
Transfer rate	2400-3B400 bps
Resolution	4mil
Revolve angle	Left/fäght 70°, Top/Down 70°
Barcode type	UPC-A, UPC-E, EAH-13/JAH-13, Code128, EAH-8/JAH-8, ISBH/ISSN, Code: Code 93, Codeff, Interleaved 2 of 5, Industrial 2 of 5, Chinese 2 of 5, CODABAR, MSI/PIESSEY, UK/PLESSEY, UCC/EANI28, China Postage
Scan depth of field	0-750mm
Bit error rate	1/800 million
Print contrast	Above 30% black
Electrical	
Voltage	DC5V±5%
Operating current	50 mA, 30 mA(Standby) , 100 mA(PK to PIO
Interfaces	PS/2, USB, RS232
Light	650nm visible laser diode
Light level	Can resistive the interference of lamp-light and sun-shining
Laser class	Meet the grade il national criteria for laser safety
Electric safety	En55022: 2006+At 2007 En55024: 1998+At: 2001+A2: 2003
IP degree	IP54
ESD protect	15KY
Environmental	
Operating temperature	-20°C ~ 60°C
Storage temperature	30°C - 90°C
Humidity	5% ~ 95% RH
Drop	Designed to withstand 1.8m drops
Physical	
Dīmensions (LxWxH)	166mm x 63mm x 88mm
Weight	178 g
Color	Grey, black
Material	ABS + EVA









PT-280 Portable Thermal Printer Genuine Quality

Specification	PT-280	
Printing mode	Thermal Printing	
Oot density	384dot/line	
Print speed	60mm/sec(max.)	
aper width	58mm	
aper diameter	50mm(max.)	
nterface	USB+Bluetooh(standard), USB+ Double Bluetooth, USB+wifi	
Barcode type	UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODEBAR, ITF, CODE93, CODE128, QR CODE	
	GB18030/BIG 5/Korean Character. ANK Character: FontA:12*24dot,FontB:9*17dot Korean/Simplified,Traditional Chinese:24*24dot	
	ESC/POS Compatible	
rinting Length	50KM	
attery	1800mA-1900mA, 7.4V rechargeable Li-ion Battery	
ower Adapter	Input:AC100-220V Output:DC9V/1A	
harging time	Around 3 hours	
luffer	Input buffer 4K bytes NV Flash 60K bytes	
imension	148.5mm(L)x86mm(W)x58.5mm(H)	
Veight	288g	
Vork Environment	Temperature: 0~45°C , Humidity:10~80%	
Storage Environment	Temperature: -10 ~ 60°C , Humidity: 10 ~ 90%	

PT-280

Portable Thermal Printer



Handheld comfort, can be linked to the chest You can clip the waist;



Easy paper loading, easy to use; Classic three-button,



USB Bluetooth interface (standard), USB + WIFI interface (optional);



LED indicates the printer abnormal, electricalThe amount of state charged with communication connections.



* Support to print a variety of bitmap, 1D, 2D OR

* LED lights indicate the printer anomalies. battery, charging and communications

*

code

connection status * Provide DLL.SDK.Demo application for free.Support customer application

development

?

www.easovation.com easovation@gmail.com +91 9624045500





Print Command	ESC/POS Compatible	
Printing Length	50KM	
Battery	2200mA, 7.4V rechargeable Li-ion Bat tery	
Power Adapter	Input:AC100-220V Output:DC9V/1A	
Charging time	3.0-5.0 hours	
Buffer	Input buffer 4K bytes NV Flash 60K bytes	
Dimension	131 mm(L)x 107 mm(W)x58 mm(H)	
Weight	350g	
Work Environment	Temperature: 0~45°C , Humidity:10~90%	
Storage Environment	Temperature: -10 ~ 50°C , Humidity: 10 ~ 90%	



Sweets Mart and Namkeen Shop – POS

www.easovation.com 09624045500

