


HLP106D 4"Thermal Transfer Label Printer

- Clamshell structure, easy media loading
- Direct thermal and thermal transfer printing applications
- Supporting 300M thermal transfer ribbon
- Double type sensors allowing to support broad range of labels
- Auto Label detection function, easy use
- TPH special designed overcoat, endure large printing volume
- With optional external paper roll holder, support supper big paper roll
- Bundled with Bartender label designer software & Seagull Windows Driver



300-meter Ribbon Capacity



Thicker Printer Head



Black & White Alternately

Specification

Item	Parameter	
Printing	Printing Method	Thermal transfer/Direct thermal
	Resolution	203dpi(8dots/mm)
	Printing Speed	4IPS Max
	Printing Width	108mm Max
	Printing Length	15-300mm
Processor	32 bit RISC CPU	
Memory	RAM	2MB
	Flash	2MB
Detection	Sensors	Adjustable reflective sensor, Fixed transmissive sensor(Central aligned), Head-up sensor, Ribbon end sensor
Media	Types	Roll-fed or Fan-fed, Die-cut or Continuous label, Tag stock, Continuous receipt paper
	Width	0.79"(20mm) – 4.65"(118mm)
	Thickness	0.003"(80um) – 0.007"(180um)
	Label Roll Diameter	5"(127mm)
	Core Diameter	1"(25.4mm), 1.5"(38mm), 3"(76.2mm)
Ribbon	Types	Wax, Wax/Resin, Resin
	Width	1.33"(33.8mm) – 4.33"(110mm)
	Length	984'(300m)
	Core Diameter	1"(25.4mm)
Programming Language		TSPL Simulation
Software	Label Design	HPRT Bartender UltraLite
	Driver	Windows 2000,XP,Vista7,8,10 by Seagull

Resident Fonts	Bitmap Fonts	9x17, 12x24 full ASCII character set
Code Pages		35
Barcode	1D	20
	2D	PDF417, Maxicode, DataMatrix, QR Code, Aztec
Interfaces	Standard version	USB
	Optional version	USB and Ethernet ports
Control Panel		Two bi-color LEDs for Ready and Status indication One Feed button
Power		AC/DC switching power adapter I/P: AC100-240V, 50/60Hz, O/P: DC 24V/2A, peak 5A
Environment	Operation	41°F(5°C)-104°F(40°C), 30%-85%, non-condensing
	Storage	-4°F(-20°C)-122°F(50°C), 10%-90%, non-condensing
Physical	Dimension	285(L)*226(W)*171(H)mm
Characteristics	Weight	2.26kg, excluding consumables
Options & Accessories		External label roll holder for 8" (203mm) OD label rolls
Agency Approvals		FCC, CE



Logistic



Medical



Retail



Healthcare



Barcode



Security



Hospitality & Leisure



Windows



Manufacturing