



**MAXIM  
PERIPHERALS PVT. LTD.**

## **Cash Drawer 4B8C**



### **Features :**

- Adjustable 4 Bills 8 Coins
- 410(W) x 420(D) x 100 (H) mm
- 3-Position lock, 1 or 2 media slots
- Voltage 12V/24V, Cable : 100-150cm length
- Thick gauge cold rolled steel & SECC
- RJ11 or RJ12 as standard

### **Specifications :**

#### **Physical**

|              |   |                                                           |
|--------------|---|-----------------------------------------------------------|
| Dimension    | : | 410(W)x420(D)x100(H) mm / 16.1(W) x 16.5(D) x 3.9(H) inch |
| Construction | : | 1.0mm thick metal construction                            |
| Finish       | : | Textured hybrid power coat                                |
| Color        | : | Black, beige and custom type                              |
| Roller       | : | Polyurethane for smooth operation                         |

#### **Cash Tray (Insert)**

|                  |   |                                                      |
|------------------|---|------------------------------------------------------|
| Construction     | : | Shatter-resistant plastic (ABS Plastic)              |
| Currency Layout: | : | Bill Metal Wire Grippers, adjustable coin slots 4B8C |
| Media Slots      | : | 1 & 2                                                |

#### **Operation**

|           |   |                                                                                                         |
|-----------|---|---------------------------------------------------------------------------------------------------------|
| Lock      | : | 3-position lock/4 functions : Locked open/closed, manual open, electronically driven, Emergency Switch. |
| Interface | : | RJ11 or RJ12 as standard                                                                                |

#### **Net Weight**

|              |   |                  |
|--------------|---|------------------|
| Net Weight   | : | 6.3Kg            |
| Gross Weight | : | 7.3 Kg.          |
| Carton Size  | : | 475x465x165 (mm) |