

PS-3316E



Slim and Flexible

Streamlined design equips with a foldable base; PS-3316E provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal top and the base, PS-3316E ensures neat, reliable peripheral cabling.

Specification	PS-3316E
Processor	Intel J1900 processor, 2.00GHz/2.42GHz (Burst), 2M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 8GB
Storage Device	1 x SATA + 1 x eMMC connector, SATA SSD default
Power Supply	12V/40W
OS Support	Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/POSReady 7/Linux per request

Display	
LCD Display	15.6" TFT LCD, Default 1024 x 768, 1366 x 768 max.
Touch Function	5-wire resistive touch

Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	4 x DB9, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
UPS Port	N/A
Standard USB Port	5
PS/2 Port	1, via optional conversation cable
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
Audio	Buzzer only
WIFI	Optional internal mini-PCIe WIFI module with PIFA Antenna

Physical Dimension	
Dimension [W x D x H in mm]	372 x 320 x 252.7
Weight [N.W. in Kg]	4.7

Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Options	
SA-105	Side Attachment for PS Series with 3 track MSR
SA-205	Side Attachment for PS Series with iButton
SA-305	Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
SA-505	3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series
LM-6807U/LM-6810U	7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface)
PD-2609UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-360UE/PD-360R	2 x 20 LCD, rear-mount, USB with Virtual COM support (PD-360UE)/RS232(PD-360R)
PD-6807U	7" color LCD graphical line display, rear-mount (USB interface)
KP-500	40-key dynakey attachmentwith MSR or RFID option for 15"/17" XT series & 15"/15.6" PS series

* The product information and specifications are subject to change without prior notice.
* Please refer to the web site for more attachment options.

U.S Patent 9004436

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

2016Q1



POSIFLEX Technology (India) Pvt Ltd., (India HQ)

985, 1st A Main Rd, 4th Cross, New Thippasandra, Bangalore 560 075.
Tel : +91 80 4078 2700 E-mail : Sales@posiflexindia.com
Fax : +91 80 4153 6089 Http://www.posiflexindia.com

POSIFLEX Technology Inc. (Global HQ)

Add No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

Authorized Distributor / Reseller

A Robust, Economic Choice



PS-3316E

Best Value Fanless POS Terminal

PS-3316E is a 15.6" wide touchscreen fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represent one of the best value choices in the entry-level POS Terminal segment.