Gprinter®

PT-280

Portable Thermal Printer

Genuine Quality

Specification	PT-280
Printing mode	Thermal Printing
Dot density	384dot/line
Print speed	60mm/sec(max.)
Paper width	58mm
Paper diameter	50mm(max.)
Interface	USB+Bluetooth(standard), USB+ Double Bluetooth, USB+wifi
Barcode type	UPC-A, UPC-E, EAN13(JAN13), EAN8(JAN8), CODE39, CODEBAR, ITF, CODE93, CODE128, DR CODE
Character font	GB18030/BIG-5Korean Character, ANK Character: Font A 12*24dot,Font B 9*17dot Korean/Simplified,Traditional Chinese:24*24dot
Print Command	ESC/POS Compatible
Printing Length	50KM
Battery	1800mA-1000mA, 7.4V rechargeable Li-ion Battery
Power Adapter	Input:AC100-220V Output:DC9V1A
Charging time	Around 3hours
Buffer	Input buffer:4K bytes NV Flash:50K bytes
Dimension	148.5mm(L)x86mm(W)x50.5mm(H)
Weight	286g
Work Environment	Temperature: 0~40℃ , Humidity: 10~80%
Storage Environment	Temperature: -10~50℃ , Humidity: 10~90%

PT-280 Portable Thermal Printer

Handheld comfort, can be linked to the chest
You can clip the waist

Easy paper loading, easy to use.
Classic three-button.

USB Bluetooth interface (standard).
USB + WiFi interface (optional)

LED indicates the printer abnormal, electrical the amount of state charged with communication connections.