

- 2.4G Wireless Communication technology, effective range up to 100 meters.
- Built in 1400 mAH battery.
- Can Store up to 100,000 barcodes.
- 32 Bits CPU super decoding ability.





For 1D Barcodes

# The DCode Advantage

QUICK DEPENDABLE TOUGH

From the distribution centre to the point-of-sale, you need convenient, precise data capture. Regardless of your industry or the kind of barcode scanner you need, you'll be able to find it in our vast portfolio.

Our technology and constant innovation enhances customer experience, improves overall productivity/profitability and amplifies supply chain efficiency.

#### **Cordless Scanner improves Mobility**

DC5112 gives superlative barcode scanning in a strong future-proof device that delivers an outstanding total cost of ownership. Workers can move within 100 m radius to scan items — and the elimination of hazardous cables creates a safer work environment. From cashiers moving around the register to scan large, heavy items and check for missed items to healthcare workers double checking that the right patient is receiving the right medication, DC5112 provides reliable and secure wireless transmission of data between the scanner and your host. Productivity is improved, revenues are protected and potential liability due to injury from lifting heavy objects is reduced.

# Reduces the requirement for training

Easy to use and handle, DC5112 requires minimal set up time and effort. From the very moment the scanner is unboxed, people can easily use the Barcode Scanner throughout the day due to its light structure, speed and simple design. In Short, DC5112 is an efficient laser Scanner that terminates delays in scan-intensive applications.

### **Exceptional Value for everyday use**

Intended to address the needs of small businesses, DC5112 provides the performance and features needed to altogether reduce data entry mistakes and boost efficiency every day in gift shops, boutiques, outdoor supplies, gem specialists, video stores, florists and other nearby retailers. Simple and comfortable to handle, this high-value low cost scanner offers the unwavering quality and investment security.

BARCODE SCANNER

#### Proven Quality you can trust

When you buy DC5112, you get the additional affirmation of buying an item of global quality adhering to global standards of quality and use.

It comes with a factory warranty of 1 Year to give you added peace of mind.



# **SPECIFICATION**

| Physical Characteristics |                  |
|--------------------------|------------------|
| Colour                   | Twilight Black   |
| Material                 | ABS+PC           |
| Single Pack Size         | 167mm*80mm*100mm |
| Single Gross Weight      | 0.28 kg          |

| Electrical      |              |
|-----------------|--------------|
| Working current | 3.5Vx40mA    |
| Standby current | 18uA-5mA     |
| Charging Power  | 5V-400mA     |
| Battery         | 3.7V-1400mAH |

| Wireless Connectivity |                                    |
|-----------------------|------------------------------------|
| Transmission mode     | 2.4G Wireless                      |
| Radio Range           | 330 ft./100 meters (line of Sight) |

| Scan Performance  |   |
|-------------------|---|
| Scanning type     | bi-directional  |
| Light Source      | 650 nm Visible diode  |
| Decoding Speed    | 300 Scans/sec   |
| Scanning Width    | 30cm  |
| Printing Contrast | ≥25%  |
| Reading Angle     | Angle of Rotation ±30°,<br>Inclination ±45°, declination ±60°   |
| Indication        | Buzzer & LED  |
| Trigger Mode      | Button, Continuous,<br>Auto-Indication  |
| Storage           | 100,000 barcodes  |
| СРИ               | ARM 32-bit Cortex   |
| BER               | 1/20 million  |
| Anti-Interference | No Influence working under string light and sunshine  |
| Decode Capability | UPC/EAN, with complimentary<br>UPC/EAN, Code 128, Code 39,<br>Code 39 Full ASCII, Codabar,<br>industrial/interleaved 2 of 5 Code<br>93, MSI, Code 11, ISBN, ISSN,<br>China Post, GS1 Databar, Code 32 |

| Depth of Field   |                    |
|--|--------------------|
| Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. |                    |
| 3 mils   | 2.0mm to 100.0 mm  |
| 10 mils  | 2.0mm to 350.0 mm  |
| 15 mils  | 5.0mm to 500.0 mm  |
| 30 mils  | 10.0mm to 800.0 mm |

| User Environment      |   |
|-----------------------|---|
| Operating Temperature | 0°C to 50°C   |
| Storage Temperature   | -40°C to 70°C   |
| Humidity              | 5% to 95% relative humidity, non-condensing                   |
| Drop                  | Designed to resist 2 meter drop                               |
| Environmental Sealing | IP54  |
| ESD                   | Confirms to 15 kv air discharge and 8 kv of contact discharge |

# Warranty

DC 5112 (1D WIRLESS) is warranted against defects in workmanship and materials for a period of 1 year from the date of shipment, provided the product remains unmodified and is operated under normal and proper condition

| Packing Details |   |
|-----------------|---|
| Standard List   | Scanner*1, Cable*1, Manual*1,<br>Setting Card*1, RF Receiver *1 |
|                 | Setting Card*1, RF Receiver *1                                  |

